

DECLARATION OF PERFORMANCES

Nº: 500582

1. **Product:**
CORKLAND
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:** Light mortar, type CT C16 F3, for floor screed and rehabilitation of old slabs, up to 5cm thick, with additional insulation to impact noise.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type A1	EN-13813:2014
Emission of harmful substances	CT	
Water permeability	NPD	
Water vapour permeability	NPD	
Compressive Strength	C16	
Flexural Strength	F3	
Wear Strength	NPD	
Sound insulation	NPD	
Acoustic absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5. This declaration of features is issued under the sole responsibility of manufacturer stated in point 2, in accordance with Regulation (EU) No 305/2011.

Signed by and on manufacturer behalf

Place and date of issue: Cordoba, 21/10/2022



Technical director: José A. Ferre Martínez



GRUPO PUMA ESPAÑA S.L
 Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
 14014 CÓRDOBA
 22

CORKLAND
Nº: 500582
EN 13813

Light mortar, type CT C16 F3, for floor screed and rehabilitation of old slabs, up to 5cm thick, with additional insulation to impact noise.

Reaction to fire Classe A1

Emission of harmful substances CT

Compressive Strength C16

Flexural Strength F3

Hazardous substances See safety datasheet