


**DECLARATION DE PERFORMANCES**  
**Nº: 803525-01**

1. **Product:**  
MORCEM RENOVEX F
2. **Manufacturer:**  
GRUPO PUMA SL, located in:  
Avda Agrupación Córdoba 17,  
14014 Córdoba  
[www.grupopuma.com](http://www.grupopuma.com)
3. **Intended use:** Product for surface protection–coating. Mineral mortar for regularization, leveling and smoothing of fine finish, on absorbent and non-absorbent surfaces, for interiors and exteriors in white.
4. **Evaluation system:**  
4
5. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Water vapour permeability	Type A1	EN 1504-2:2005
Capillary absorption and water permeability	$\leq 0.3 \text{ Kg/m}^2 \cdot \text{h}^{0.5}$	
Thermal compatibility part 1 and 4	$>2.0 \text{ N/mm}^2$	
Adhesive force by tensile test	$>2.0 \text{ N/mm}^2$	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5.  
 This declaration of features is issued under the sole responsibility of manufacturer stated in point 2, in accordance with Regulation (EU) No 305/2011.

Signed by and on manufacturer behalf  
 Place and date of issue: Córdoba, 05/04/2021



Technical director: José A. Ferre Martínez



GRUPO PUMA S.L  
 Avda. Agrupación Córdoba 17  
 14014 Córdoba  
 16

**MORCEM RENOVEX F**  
**Nº: 803525-01**  
**EN 1504-2**

Product for surface protection–coating. Mineral mortar for regularization, leveling and smoothing of fine finish, on absorbent and non-absorbent surfaces, for interiors and exteriors in white.

<b>Water vapour permeability</b>	Type A1
<b>Capillary absorption and water permeability</b>	≤ 0.3 Kg/m <sup>2</sup> ·h <sup>0.5</sup>
<b>Thermal compatibility part 1 and 4</b>	>2.0 N/mm <sup>2</sup>
<b>Adhesive force by tensile test</b>	>2.0 N/mm <sup>2</sup>